Nov. 2005

THE SPECIFICATION OF AlGaAs IR LED CHIP "IR4C"

1. DESCRIPTION

This is a AlGaAs red LED chip. It is N-side up. The peak wavelength is 810 nm (Typ.).

2. ELECTRO - OPTICAL CHARACTERISTICS (Ta=25deg. C)

CONDITION			MIN.	TYP.	MAX.	UNIT
Forward Voltage	(V_F)	IF=20mA		1.65		V
Reverse Voltage	(V_R)	IR=10uA	5			V
Radiated Power[1)]	(Po)	IF=20mA	1.0			mW
Peak Wavelength	(λ_P)	IF=20mA	800	810	820	nm
Spectral Radiation Bandwidth	($\Delta\lambda$)	IF=20mA		30		nm

1) LED chip is mounted on TO-18 gold header without resin coated.

3. ABSOLUTE MAXIMUM RATINGS

Continuous Maximum Forward Current : 100 mA(DC)
Reverse Voltage : 5 V(IR=10uA)
Storage Temperature
while on mylar membrane : 0 to 40 deg. C
after removal from mylar membrane : -40 to 100 deg. C

4. PHYSICAL CHRACTERISTICS AND STRUCTURE

1) Material : AlGaAs
2) Structure : Double Hetero Structure
3) Junction Size : 0.370mmX0.370mm
4) Thickness : 0.150mm
5) Bond Pad Size : 0.140mm diameter
6) Anode Metallization : Gold Alloy
7) Cathode Metallization: Gold Alloy

Nov. 2005

Physical Dimensions

Model IR4C

Unit: um



Remark: This specification is for reference purpose only, and subject to change without prior notice.
Approved specification shall be obtained for the regular purchase.